



SPECIFICATION SHEET
NLB1P400PSUNV



- Line Voltage: 120-277V 50/60Hz
- Lamp End of Life Protection
- Program Start
- Active Power Factor Correction
- Type CC



Lamp Type		Min. Start Temp. (°F/°C)	Vin (V)	Iin (A)	Pin (W)	ATHD ≤%	PF ≥	CF ≤
Type	No.							
T5 UVC36"	1	-20/-29	120	0.48	58	10	0.98	1.70
T5 UVC30"	2	-20/-29	120	0.40	49	10	0.98	1.70
T5 UVC20"	3	-20/-29	120	0.26	32	10	0.98	1.70
T5 UVC16"	4	-20/-29	120	0.21	25	10	0.98	1.70
T5 UVC36"	5	-20/-29	277	0.21	58	10	0.98	1.70
T5 UVC30"	6	-20/-29	277	0.18	48	10	0.95	1.70
T5 UVC20"	7	-20/-29	277	0.12	31	15	0.95	1.70
T5 UVC16"	8	-20/-29	277	0.10	25	15	0.95	1.70

Note: the above data is tested at 60Hz.

Application and Performance Specification Information Subject to Change without Notification.

Performance

- Meets ANSI Standard C82.11-2002
- Meets ANSI Standard C62.41-2002
- Meets FCC 18 Non-CONSUMER Limits

Safety

- No PCBs, Type HL
- UL listed (Class P, Type 1 Outdoor)
- OCV : 300V
- No-load Power : 0.2W

Application

- Maximum Ambient Temperature: 131°F, 55°C
- Remote Mounting: 18 ft. max. Lead length, 18AWG
- Sound Rated: A
- Maximum case temperature Tc: 167°F, 75°C

Physical Parameters

- Length 9.75"/248mm
- Width 1.5"/38mm
- Height 1.2"/31mm
- Mounting 8.9"/226mm
- Weight 1.3 lbs

Lead Length

- White, Black 18"(±1")
- Red/ Blue 32"(±1")



SPECIFICATION SHEET

NLB1P400PSUNV

