



# SPECIFICATION SHEET

## NLB2S26PSUNV-C



- Line Voltage: 120-277V 50/60Hz
- Series Lamp Operation
- Lamp End of Life Protection
- Program Start
- Active Power Factor Correction
- Type CC



Lamp Type			Min. Start Temp. (F/C)	Vin (V)	Iin (A)	Pin (W)	ATHD ≤%	PF ≥	CF <	BF	BEF
Type	No.	Watts									
* CFQ26W	2	26	0/-18	120	0.47	57	10	0.98	1.70	0.88	1.54
TL5C	2	22	0/-18	120	0.37	44	10	0.98	1.70	0.76	1.84
CFQ26W	1	26	0/-18	120	0.25	30	10	0.98	1.70	0.81	2.69
CFTR42W	1	42	0/-18	120	0.34	40	10	0.98	1.70	0.88	1.76
CFTR32W	1	32	0/-18	120	0.27	33	10	0.98	1.70	0.82	2.20
FT36	1	36	0/-18	120	0.27	33	10	0.98	1.70	0.73	2.04
TL5C/40W	1	40	0/-18	120	0.28	34	10	0.98	1.70	0.74	1.86
TL5C/32W	1	32	0/-18	120	0.26	31	10	0.98	1.70	0.82	2.63
TL5C/22W	1	22	0/-18	120	0.19	23	10	0.98	1.70	0.74	3.51
TL5C/40W+22W	1+1	40+22	0/-18	120	0.44	53	10	0.98	1.70	0.82	1.32
TL5C/22W+32W	1+1	22+32	0/-18	120	0.41	50	10	0.98	1.70	0.73	1.56
* CFQ26W	2	26	0/-18	277	0.21	53	10	0.97	1.70	0.97	1.73
TL5C	2	22	0/-18	277	0.16	44	10	0.97	1.70	0.76	1.99
CFQ26W	1	26	0/-18	277	0.11	30	10	0.97	1.70	0.82	2.72
CFTR42W	1	42	0/-18	277	0.15	42	10	0.97	1.70	0.89	1.81
CFTR32W	1	32	0/-18	277	0.14	39	10	0.97	1.70	0.80	2.21
FT36	1	36	0/-18	277	0.14	39	10	0.95	1.70	0.73	2.02
TL5C/40W	1	40	0/-18	277	0.13	36	10	0.95	1.70	0.75	1.87
TL5C/32W	1	32	0/-18	277	0.11	30	10	0.95	1.70	0.72	2.40
TL5C/22W	1	22	0/-18	277	0.09	25	10	0.90	1.70	0.74	3.53
TL5C/40W+22W	1+1	40+22	0/-18	277	0.19	53	10	0.97	1.70	0.81	1.47
TL5C/22W+32W	1+1	22+32	0/-18	277	0.18	50	10	0.97	1.70	0.74	1.61

Note: the above data is tested at 60Hz. Application and Performance Specification Information Subject to Change without Notice.

\*UL&cUL is in application



SPECIFICATION SHEET  
 NLB2S26PSUNV-C



**Performance**

Meets ANSI Standard C82.11-2002  
 Meets ANSI Standard C62.41-2002  
 Meets FCC 18 Non-CONSUMER Limits

**Safety**

No PCBs,  
 UL listed (Class P, Type 1  
 Outdoor) OCV 300V  
 No-load Power < 5W

**Application**

Maximum Ambient Temperature: 131°F,55°C  
 Remote Mounting: 18 ft. max. Lead length,  
 18AWG Sound Rated: A  
 Maximum case temperature Tc: 194°F,90°C

**Physical Parameters**

Length	5.05"	128.3(mm)
Width	2.42"	61.4(mm)
Height	0.9"	23.0(mm)
Mounting	4.66"	118.4(mm)
Weight	0.48 lbs / 220g	

